## NSN 5930-01-251-4890

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-251-4890

| Body Style:   |
|---|
| Panel mounted   |
| Hazardous Locations/environmental Protection:                   |
| Explosion proof and humidity resistant                          |
| Overall Length:   |
| 3.430 inches  |
| Overall Height:   |
| 1.000 inches  |
| Overall Width:  |
| 0.750 inches  |
| Body Width:   |
| 0.750 inches  |
| Body Height:  |
| 0.750 inches  |
| Case Material:  |
| Metal   |
| Actuator Length:  |
| 0.890 inches  |
| Actuator Style:   |
| Rectangular   |
| Actuator Height:  |
| 0.430 inches  |
| Actuator Width:   |
| 0.640 inches  |
| Actuator Color:   |
| Black single actuator   |
| Illuminated Actuator Color:                                     |
| Red single actuator and green single actuator                   |
| Actuator Inscription:   |
| Lateral speed single actuator                                   |
| Maximum Voltage Rating In Volts:                                |
| 28.0 dc   |
| Mounting Surface To Terminal End Distance:                      |
| 2.950 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Panel   |
| Features Provided:  |
| Full display lens   |
| Nonpile-up Contact Arrangement:                                 |
| 2 pole, double throw, one position momentary single switch unit |

## NSN 5930-01-251-4890

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Precious Material And Location:** 

Contacts gold

**Terminal Type And Quantity:** 

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0