# NSN 5930-01-251-4894

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-251-4894

#### **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

3.440 inches

#### **Overall Height:**

1.250 inches

#### **Overall Width:**

1.000 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

1.000 inches

#### Case Material:

Metal

# Actuator Length:

0.890 inches

# Actuator Style:

Rectangular

#### Actuator Height:

0.430 inches

#### Actuator Width:

0.640 inches

#### Actuator Color:

Black single actuator

#### Illuminated Actuator Color:

Red single actuator and green single actuator

#### **Actuator Inscription:**

Primary heading single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc

## Mounting Surface To Terminal End Distance:

2.950 inches

## Inclosure Type:

Fully enclosed

# Mounting Method:

Panel

## **Features Provided:**

Full display lens

## Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

# NSN 5930-01-251-4894

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

# Precious Material And Location:

Contacts gold

# Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

## Fiig:

A053a0