## NSN 5930-01-251-8060

Pressure Switch - Page 1 of 2

Rectangular



View Online at https://aerobasegroup.com/nsn/5930-01-251-8060

Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
4.100 inches
Overall Height:
5.250 inches
Body Height:
4.100 inches
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -30.0 degrees fahrenheit and 140.0 degrees fahrenheit
Features Provided:
Electrical access port
Contact Action Stimulus:
Decrease
Nonpile-up Contact Arrangement:
2 pole, single throw, normally closed, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
1.5 amperes resistive load first voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:
+40.00/+83.00 actuation point pounds per square inch gage and +72.00/+100.00 deactuation point pounds per square inch gage
Contact Adjustment Type:
Internal actuation point screw and internal deactuation point screw
Contact Voltage Rating In Volts:
230.0 dc at sea level third voltage
Pressure Connector Type:
Flared, threaded external single connection
Frequency In Hertz:
60.0 single voltage
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:

## NSN 5930-01-251-8060

Pressure Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0