

View Online at <https://aerobasegroup.com/nsn/5930-01-251-8066>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.880 inches

**Body Length:**

1.090 inches

**Body Width:**

0.400 inches

**Body Height:**

0.630 inches

**Unthreaded Mounting Hole Diameter:**

0.110 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.410 inches

**Actuator Length:**

0.110 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

0.170 inches

**Actuator Free Position Height:**

0.578 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

15.0 grams

**Switch Actuating Force:**

135.0 grams

**Actuator Movement:**

Between 0.047 pretravel inches and 0.050 overtravel inches and 0.002 differential inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 10.000 amperes resistive ac and 3.000 amperes lamp ac

**Terminal Type And Quantity:**

3 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0