

View Online at <https://aerobasegroup.com/nsn/5930-01-251-8066>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.880 inches

Body Length:

1.090 inches

Body Width:

0.400 inches

Body Height:

0.630 inches

Unthreaded Mounting Hole Diameter:

0.110 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.410 inches

Actuator Length:

0.110 inches

Actuator Style:

Rectangular

Actuator Width:

0.170 inches

Actuator Free Position Height:

0.578 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

15.0 grams

Switch Actuating Force:

135.0 grams

Actuator Movement:

Between 0.047 pretravel inches and 0.050 overtravel inches and 0.002 differential inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 10.000 amperes resistive ac and 3.000 amperes lamp ac

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0