

View Online at <https://aerobasegroup.com/nsn/5930-01-251-8067>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.190 inches

**Body Length:**

0.500 inches

**Body Width:**

0.200 inches

**Body Height:**

0.350 inches

**Unthreaded Mounting Hole Diameter:**

0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.060 inches

**Actuator Free Position Height:**

0.320 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**End Application:**

6920-01-128-1304 training section, st

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.003 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.000 amperes inductive dc and 5.000 amperes resistive ac

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0