## NSN 5930-01-252-0450

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-252-0450 **Overall Length:** 1.969 inches **Body Length:** 1.500 inches **Overall Diameter:** 1.094 inches **Pressure Switch Type:** Gage **Operating Tempurature Rating:** Between -65.0 degrees fahrenheit and 225.0 degrees fahrenheit **Mounting Method:** Threaded bushing **Contact Action Stimulus:** Increase **Proof Pressure:** 50.00 pounds per square inch **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Terminal Type:** Tab w/screw **Contact Load Current Rating:** 1.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage **Contact Adjustability:** Actuation point adjustable and deactuation point adjustable **Contact Adjustment Range:** +3.00/+50.00 actuation point pounds per square inch gage and +2.00/+48.00 deactuation point pounds per square inch gage **Contact Adjustment Type:** External actuation point hex nut and external deactuation point hex nut **Contact Voltage Rating In Volts:** 28.0 dc at sea level second voltage **Special Features:** Turn switch in clockwise direction will lower set point Frequency In Hertz: 60.0 first voltage Media For Which Designed: Gas **Precious Material And Location:** Terminals gold **Precious Material:** 

Gold
Style D

**Style Designator:** 

Cylindrical

## NSN 5930-01-252-0450

Pressure Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0