

View Online at <https://aerobasegroup.com/nsn/5930-01-252-0682>

Hazardous Locations/environmental Protection:

Explosion proof and moisture resistant and shock resistant and vibration resistant

Overall Length:

0.842 inches

Overall Height:

1.770 inches

Overall Width:

1.150 inches

Unthreaded Mounting Hole Diameter:

0.080 inches single mounting facility

Distance Between Mounting Facility Centers:

0.905 inches single mounting facility

Individual Section Quantity:

1

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel single actuator

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

16 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

Ex, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15 single section

Contact Arrangement Truth Table:

Binary with common not-true bits, 2 pole - 16 positions single section

Color:

White single indicator marking

Style Designator:

Rectangular indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0