

View Online at <https://aerobasegroup.com/nsn/5930-01-252-0682>

<b>Hazardous Locations/environmental Protection:</b>
Explosion proof and moisture resistant and shock resistant and vibration resistant
<b>Overall Length:</b>
0.842 inches
<b>Overall Height:</b>
1.770 inches
<b>Overall Width:</b>
1.150 inches
<b>Unthreaded Mounting Hole Diameter:</b>
0.080 inches single mounting facility
<b>Distance Between Mounting Facility Centers:</b>
0.905 inches single mounting facility
<b>Individual Section Quantity:</b>
1
<b>Operating Tempurature Range:</b>
-65.0/+85.0 degrees celsius
<b>Mounting Method:</b>
Bracket single mounting facility and unthreaded hole single mounting facility
<b>Actuator Type:</b>
Thumbwheel single actuator
<b>Contact Voltage Rating In Volts:</b>
28.0 dc at sea level
<b>Mounting Facility Pattern:</b>
Two position in-line single mounting facility
<b>Switch Actuator Indexing Position Quantity:</b>
16 single actuator
<b>Terminal Type:</b>
Printed circuit
<b>Contact Load Current Rating:</b>
125.0 milliamperes resistive load dc at sea level
<b>Readout Indicator Marking:</b>
Ex, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15 single section
<b>Contact Arrangement Truth Table:</b>
Binary with common not-true bits, 2 pole - 16 positions single section
<b>Color:</b>
White single indicator marking
<b>Style Designator:</b>
Rectangular indicating
<b>Shelf Life:</b>
N/a
<b>Unit Of Measure:</b>
--

**Demilitarization:**

No

**Fiig:**

A052b0