

View Online at <https://aerobasegroup.com/nsn/5930-01-252-1304>

Body Style:

Panel mount

Overall Length:

0.750 inches

Overall Height:

2.320 inches

Overall Width:

0.750 inches

Body Length:

0.688 inches

Body Width:

0.688 inches

Body Height:

2.080 inches

Actuator Style:

Rectangular

Actuator Height:

0.150 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

White single actuator and red single actuator and red single actuator

Actuator Inscription:

S fwd lubo v; op; cl single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Emi shielded; anvis feature; red night legend lighting; -way split lens

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 tab, solder lug and 6 turret

Specification Data:

53711-438-5750357 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0