NSN 5930-01-252-1314

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-252-1314

Body Style:
Panel mount
Overall Length:
0.750 inches
Overall Height:
2.360 inches
Overall Width:
0.750 inches
Body Length:
0.750 inches
Body Width:
0.680 inches
Body Height:
2.120 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.150 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator and black single actuator and black single actuator
Illuminated Actuator Color:
Black single actuator and black single actuator and black single actuator
Actuator Inscription:
P tank valve/op/cl single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
3 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes

inductive ac and 2.000 amperes lamp ac **Special Features:**

Three-way split lens; actuator inscription characters are green when illuminated

NSN 5930-01-252-1314

Push Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
9 turret and 6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Domilitarization:

No

Fiig:

A053a0