NSN 5930-01-252-2892

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-252-2892

- **Body Style:**
- Panel mount
- **Overall Length:**
- 0.750 inches
- **Overall Height:**
- 2.320 inches
- **Overall Width:**
- 0.750 inches
- **Body Length:**
- 0.688 inches
- **Body Width:**
- 0.688 inches
- Body Height:
- 2.080 inches
- Actuator Style:

Rectangular

- Actuator Height:
- 0.150 inches
- **Actuator Color:**
- Black single actuator
- Illuminated Actuator Color:
- White single actuator and red single actuator
- **Actuator Inscription:**
- S main clsc, on single actuator
- Maximum Voltage Rating In Volts:
- 115.0 ac and 28.0 dc
- Inclosure Type:
- Fully enclosed
- **Mounting Method:**
- Panel
- Nonpile-up Contact Arrangement:
- 2 pole, double throw, one position momentary single switch unit
- Contact Load Current Rating At Maximum Rated Voltage:
- 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac
- **Special Features:**
- Emi shielded; anvis feature; red night legend lighting; split lens
- **Precious Material And Location:**
- Contacts silver
- **Terminal Type And Quantity:**
- 6 tab, solder lug and 6 turret
- Shelf Life:
- N/a

NSN 5930-01-252-2892

Push Switch - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

