## NSN 5930-01-252-2903

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-252-2903

**Body Style:** 

Panel mount

**Overall Length:** 

0.750 inches

**Overall Height:** 

2.320 inches

**Overall Width:** 

0.750 inches

**Body Length:** 

0.688 inches

**Body Width:** 

0.688 inches

Body Height:

2.080 inches

**Actuator Style:** 

### Rectangular

Actuator Height:

0.150 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

White single actuator and red single actuator

**Actuator Inscription:** 

Xfr 2 out; on single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

**Mounting Method:** 

Panel

#### Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Emi shielded; anvis feature; red night legend lighting; split lens

**Precious Material And Location:** 

Contacts silver

#### **Terminal Type And Quantity:**

6 tab, solder lug and 6 turret

**Specification Data:** 

53711-438-5750357 manufacturers source control

# NSN 5930-01-252-2903

Push Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

