

View Online at <https://aerobasegroup.com/nsn/5930-01-252-2903>

**Body Style:**

Panel mount

**Overall Length:**

0.750 inches

**Overall Height:**

2.320 inches

**Overall Width:**

0.750 inches

**Body Length:**

0.688 inches

**Body Width:**

0.688 inches

**Body Height:**

2.080 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.150 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

White single actuator and red single actuator

**Actuator Inscription:**

Xfr 2 out; on single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Special Features:**

Emi shielded; anvis feature; red night legend lighting; split lens

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

6 tab, solder lug and 6 turret

**Specification Data:**

53711-438-5750357 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0