

View Online at <https://aerobasegroup.com/nsn/5930-01-252-3920>

Hazardous Locations/environmental Protection:

Explosion resistant

Overall Length:

2.656 inches

Overall Height:

4.094 inches

Overall Width:

4.250 inches

Body Length:

2.281 inches

Unthreaded Mounting Hole Diameter:

0.312 inches

Capillary Tube Length:

84.0 inches

Bulb Length:

5.000 inches

Bulb Diameter:

0.250 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

7.375 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Capillary tube end seal connection and integral knob

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained

Terminal Type:

Tab w/screw

Contact Load Current Rating:

30.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+60.00/+250.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point knob with scale

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0