NSN 5930-01-252-3979

Flow Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-252-3979

Thread Class:
2b single threaded hole
Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
Between 3.284 inches and 3.346 inches
Overall Diameter:
0.500 inches
Mounting Method:
Bracket and threaded hole
Thready Qty Per Inch (tpi):
32 single threaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.138 inches single threaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Printed circuit
Contact Load Current Rating:
400.0 milliamperes resistive load single voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Voltage Rating In Volts:
12.0 dc at sea level single voltage
Media For Which Designed:
Gas
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Style Designator:
Cylindrical
Thread Series Designator:
Unc single threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5930-01-252-3979

Flow Switch - Page 2 of 2



Fiig:

A048b0