

View Online at <https://aerobasegroup.com/nsn/5930-01-252-4608>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Shock proof

Overall Length:

5.890 inches

Overall Height:

2.875 inches

Overall Width:

2.500 inches

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

1.062 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.062 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Contact Load Current Rating:

4.0 amperes inductive load lowest ac voltage rating at sea level

Special Features:

Legend plate reads normal bypass

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0