

View Online at <https://aerobasegroup.com/nsn/5930-01-253-4220>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Vibration resistant and shock resistant

Overall Length:

0.775 inches

Overall Height:

2.828 inches

Overall Width:

0.650 inches

Bushing Length:

0.468 inches

Body Length:

0.775 inches

Body Width:

0.650 inches

Body Height:

1.070 inches

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

1.140 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position locked out and center position no locking action

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc

Precious Material And Location:

Contact surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

16 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0