

View Online at <https://aerobasegroup.com/nsn/5930-01-253-6260>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.437 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

3.283 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.437 inches single actuator

**Overall Diameter:**

1.070 inches

**Individual Section Quantity:**

5

**Nonturn Device Type:**

Slotted bushing at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 5th section front

**Throw Quantity:**

10 3rd section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Dummy section

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 5th section

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Shaft Type:**

Round, flatted single actuator

**Criticality Code Justification:**

Zzzy

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks 5th section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Contact Load Current Rating:**

1.25 amperes resistive load dc at sea level and 250.0 milliamperes inductive load dc at sea level

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard no. Lo3672

**Precious Material And Location:**

Wave washer and thrust washer and shaft surfaces silver and contact surfaces gold

**Precious Material:**

Silver and gold

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Reference Number Differentiating Characteristics:**

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0