

View Online at <https://aerobasegroup.com/nsn/5930-01-253-8568>

**Thread Class:**

2a single mounting facility

**Overall Length:**

1.750 inches

**Overall Diameter:**

2.000 inches

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Throw Quantity:**

24 single section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 highest dc voltage rating at sea level

**Cam Actuated Switch Contact Arrangement:**

1 pole, single throw, both positions maintained single switch single section front

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section front

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level 3.0 amperes resistive load highest dc voltage rating at sea level and 2.0 amperes inductive load highest dc voltage rating at sea level

**Special Features:**

Totally enclosed; explosion-proof; unitized construction; continuous rotation

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0