

View Online at <https://aerobasegroup.com/nsn/5930-01-253-8568>

Thread Class:

2a single mounting facility

Overall Length:

1.750 inches

Overall Diameter:

2.000 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Throw Quantity:

24 single section front

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 highest dc voltage rating at sea level

Cam Actuated Switch Contact Arrangement:

1 pole, single throw, both positions maintained single switch single section front

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section front

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level 3.0 amperes resistive load highest dc voltage rating at sea level and 2.0 amperes inductive load highest dc voltage rating at sea level

Special Features:

Totally enclosed; explosion-proof; unitized construction; continuous rotation

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0