NSN 5930-01-254-2138

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-254-2138 **Thread Class:** 2a **Body Style: Bushing mount Hazardous Locations/environmental Protection:** Vibration resistant and shock resistant **Overall Length:** 3.510 inches **Overall Height:** 1.000 inches **Overall Width:** 1.000 inches **Body Diameter:** 1.000 inches **Bushing Length:** 0.470 inches **Actuator Style:** Round **Actuator Diameter:** 0.240 inches **Actuator Height:** 1.160 inches **Actuator Position-action Relationship:** Up position momentary and down position maintained **Maximum Voltage Rating In Volts:** 28.0 dc **Mounting Surface To Terminal End Distance:** 2.350 inches **Inclosure Type:** Hermetically sealed **Mounting Method:** Threaded bushing **Features Provided:** Holding solenoid Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc

NSN 5930-01-254-2138 Toggle Switch - Page 2 of 2



Thread Series Designator:
Uns
Terminal Type And Quantity:
6 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0