

View Online at <https://aerobasegroup.com/nsn/5930-01-254-2611>

Thread Class:

2a single mounting facility

Thread Length:

0.410 inches single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and corrosion resistant

Overall Length:

5.850 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.205 inches single actuator and 0.215 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.380 inches single actuator

Overall Diameter:

1.036 inches

Individual Section Quantity:

10

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Operating Temperature Range:

-67.0/+257.0 degrees fahrenheit

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 7th section front

Throw Quantity:

8 7th section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flattened single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 9th section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level

Precious Material And Location:

Rotor contacts silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0