NSN 5930-01-254-4466

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-254-4466

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.265 inches

Overall Height:

2.166 inches

Overall Width:

1.150 inches

Unthreaded Mounting Hole Diameter:

0.100 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.095 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Lever single actuator

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

6 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5 single section

Contact Arrangement Truth Table:

Bcd with complement, 1 pole - 16 positions single section

Special Features:

Factory installed stop pin to limit positions

Color:

White single indicator marking

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

NSN 5930-01-254-4466

Code Indicating Wheel Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A052b0