NSN 5930-01-254-5136

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-254-5136

| Body Style: |
|---|
| Panel mounted |
| Overall Length: |
| 2.045 inches |
| Overall Height: |
| 0.750 inches |
| Overall Width: |
| 0.750 inches |
| Body Length: |
| 1.935 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 0.750 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.620 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.110 inches |
| Actuator Width: |
| 0.620 inches |
| Actuator Color: |
| Yellow single actuator |
| Illuminated Actuator Color: |
| Yellow single actuator |
| Actuator Inscription: |
| Pnt single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Lamp holder |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |

Contact Load Current Rating At Maximum Rated Voltage: 7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

inductive ac and 1.000 amperes lamp ac

NSN 5930-01-254-5136

Push Switch - Page 2 of 2



| Precious Material And | Location: |
|-----------------------|-----------|
|-----------------------|-----------|

Contact surfaces silver

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0