NSN 5930-01-254-5234

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-254-5234

view Offilite at https://defobasegroup.com/hsh/5550-01-254-5254
Body Style:
Panel mounted
Overall Length:
2.045 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Length:
1.935 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.110 inches
Actuator Width:
0.620 inches
Actuator Color:
Yellow single actuator
Illuminated Actuator Color:
Yellow single actuator
Actuator Inscription:
Run prog single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

NSN 5930-01-254-5234

Push Switch - Page 2 of 2



Emi shielded; sunlight readable
Precious Material And Location:
Contact surfaces silver
Terminal Type And Quantity:

Special Features:

Quantity:

6 turret and 6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0