## NSN 5930-01-254-5908

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-254-5908
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Body Width:
1.000 inches
Body Height:
1.000 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.740 inches
Illuminated Actuator Color:
Red single actuator and red single actuator
Actuator Inscription:
Port on stbd on single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
1.935 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes
inductive ac and 1.000 amperes lamp ac

Special Features:

Emi shielded; 4 leds for illumination

## NSN 5930-01-254-5908

Push Switch - Page 2 of 2



**Fiig:** A053a0