NSN 5930-01-254-5908

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-254-5908
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Body Width:
1.000 inches
Body Height:
1.000 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.740 inches
Illuminated Actuator Color:
Red single actuator and red single actuator
Actuator Inscription:
Port on stbd on single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
1.935 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
$7.500 \ amperes \ resistive \ dc \ and \ 5.000 \ amperes \ inductive \ dc \ and \ 1.000 \ amperes \ lamp \ dc \ and \ 5.000 \ amperes \ resistive \ ac \ and \ 3.500 \ amperes \ and \ 3.500 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ according to the lamp \ dc \ and \ 1.000 \ amperes \ according to the lamp \ according t$
inductive ac and 1.000 amperes lamp ac

Special Features:

Emi shielded; 4 leds for illumination

NSN 5930-01-254-5908

Push Switch - Page 2 of 2



Fiig: A053a0