

View Online at <https://aerobasegroup.com/nsn/5930-01-254-7731>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Overall Length:**

2.100 inches

**Body Diameter:**

Between 0.615 inches and 0.650 inches

**Bushing Length:**

0.420 inches

**Body Length:**

1.280 inches

**Overall Diameter:**

0.633 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.375 inches

**Actuator Height:**

0.270 inches

**Actuator Color:**

Blue single actuator

**Illuminated Actuator Color:**

Blue single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.500 amperes inductive dc and 0.500 amperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes inductive ac and 0.500 amperes lamp ac

**Test Data Document:**

81349-mil-prf-22885/18 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

UNF

**Terminal Type And Quantity:**

8 tab, solder lug

**Specification Data:**

81349-mil-prf-22885/18 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0

**Mil-std (military Standard):**

Mil-prf-22885 spec.