

View Online at <https://aerobasegroup.com/nsn/5930-01-254-8205>

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

0.344 inches

**Overall Height:**

0.080 inches

**Body Diameter:**

0.263 inches

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Surface and terminal, wire-lead

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

500.0 milliamperes resistive load second voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

200.00 actuation point degrees fahrenheit and 170.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc

**Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-s-24236/13 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0