NSN 5930-01-254-8205

Thermostatic Switch - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/5930-01-254-6205
Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
0.344 inches
Overall Height:
0.080 inches
Body Diameter:
0.263 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Surface and terminal, wire-lead
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Wire lead
Contact Load Current Rating:
500.0 milliamperes resistive load second voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
200.00 actuation point degrees fahrenheit and 170.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Frequency In Hertz:
60.0 first voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Disc
Test Data Document:
81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-s-24236/13 government specification
Shelf Life:
N/a

Unit Of Measure:

NSN 5930-01-254-8205

Thermostatic Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A048b0