## NSN 5930-01-254-8208

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-254-8208

view Online at https://aerobasegroup.com/hsh/5930-01-254-6206
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
0.750 inches
Overall Height:
2.045 inches
Overall Width:
0.750 inches
Body Length:
0.750 inches
Body Width:
0.750 inches
Body Height:
1.935 inches
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.110 inches
Actuator Width:
0.620 inches
Actuator Color:
Yellow single actuator
Illuminated Actuator Color:
Yellow single actuator
Actuator Inscription:
Pct rf pwr single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

**Special Features:** 

Emi shielded; sunlight readable

inductive ac and 1.000 amperes lamp ac

## NSN 5930-01-254-8208

Push Switch - Page 2 of 2



Precious Material And Location
--------------------------------

Contact surfaces silver

**Terminal Type And Quantity:** 

12 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0