# NSN 5930-01-254-9994

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-254-9994

## **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Corrosion resistant

## **Overall Height:**

1.000 inches

### **Overall Width:**

1.000 inches

#### **Body Width:**

1.000 inches

#### **Body Height:**

1.000 inches

#### **Case Material:**

Metal

#### Actuator Length:

#### 0.740 inches

Actuator Style:

Rectangular

### Actuator Height:

0.270 inches

# Actuator Width:

0.740 inches

#### Illuminated Actuator Color:

Red single actuator

#### **Actuator Inscription:**

Remote off single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Mounting Surface To Terminal End Distance:

1.935 inches

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

#### Features Provided:

Full display lens

#### **Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

inductive ac and 1.000 amperes lamp ac

# **Special Features:**

Emi shielded; 4 leds for illumination

# NSN 5930-01-254-9994

Push Switch - Page 2 of 2



**Precious Material And Location:** 

Contacts silver

# Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A053a0