

View Online at <https://aerobasegroup.com/nsn/5930-01-255-2473>

Body Style:

Bushing mounted

Actuator Style:

Roller plunger

Actuator Free Position Height:

0.657 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.120 inches

Housing Diameter:

1.000 inches

Housing Length:

1.475 inches

Housing Bushing Length:

0.657 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Missile mx peacekeeper

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Switch Release Force:

48.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

Between 72.0 ounces and 144.0 ounces

Actuator Movement:

0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Special Features:

Weapon system essential

Precious Material And Location:

Contacts silver and contact surfaces gold

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0