## NSN 5930-01-255-2473

Sensitive Switch - Page 1 of 2

**Body Style:** 

Bushing mounted **Actuator Style:** 



View Online at https://aerobasegroup.com/nsn/5930-01-255-2473

Roller plunger
Actuator Free Position Height:
0.657 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.120 inches
Housing Diameter:
1.000 inches
Housing Length:
1.475 inches
Housing Bushing Length:
0.657 inches
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
Missle mx peacekeeper
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Switch Release Force:
48.0 ounces
Criticality Code Justification:
Feat
Switch Actuating Force:
Between 72.0 ounces and 144.0 ounces
Actuator Movement:
0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 500.000 milliamperes inductive dc
Special Features:
Weapon system essential
Precious Material And Location:
Contacts silver and contact surfaces gold
Terminal Type And Quantity:
6 screw

## NSN 5930-01-255-2473

Sensitive Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0