

View Online at <https://aerobasegroup.com/nsn/5930-01-255-4302>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Hazardous Locations/environmental Protection:

Salt spray resistant and shock resistant and vibration resistant

Overall Length:

3.906 inches

Overall Height:

2.350 inches

Overall Width:

2.350 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.438 inches 1st actuator

Nonturn Device Radius:

0.531 inches at 12: 00 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Tab at 12: 00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

300.0 highest ac voltage rating at sea level

Switch Actuator Indexing Position Quantity:

3 all actuators

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees all actuators

Detent Rotational Torque Range:

+1.500/+6.000 inch-pounds all actuators

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0