

View Online at <https://aerobasegroup.com/nsn/5930-01-255-5049>

Hazardous Locations/environmental Protection:

Corrosion resistant and humidity resistant and vibration resistant

Overall Length:

3.000 inches

Outside Diameter:

0.250 inches single connection

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Body Length:

1.850 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -60.0 degrees fahrenheit and 130.0 degrees fahrenheit

Mounting Method:

Clamp

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

1500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

7.0 amperes resistive load third voltage and 4.0 amperes inductive load third voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

12.00 actuation point pounds per square inch and 9.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Pressure Connector Type:

Flareless, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0