NSN 5930-01-255-6165

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-255-6165

| · |
|---|
| Body Style: |
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Dustproof and driptight |
| Body Length: |
| 0.688 inches |
| Body Width: |
| 0.688 inches |
| Body Height: |
| 1.820 inches |
| Actuator Length: |
| 0.960 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.450 inches |
| Actuator Width: |
| 0.960 inches |
| Actuator Color: |
| Black single actuator |
| Illuminated Actuator Color: |
| Red single actuator and red single actuator |
| Actuator Inscription: |
| Afff, on; push to, secure single actuator |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Actuator seal |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 7.000 amperes resistive dc and 4.000 amperes inductive dc |
| Special Features: |
| Horizontal split lens |
| Precious Material And Location: |
| Contacts silver |
| Terminal Type And Quantity: |

6 turret and 5 tab, solder lug

NSN 5930-01-255-6165

Push Switch - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0