NSN 5930-01-255-6166

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-255-6166

- **Body Style:**
- Panel mounted
- **Body Width:**
- 0.850 inches
- **Body Height:**
- 1.090 inches

Actuator Length:

- 1.040 inches
- **Actuator Style:**
- Rectangular
- **Actuator Height:**
- 0.140 inches
- Actuator Width:
- 0.800 inches
- **Actuator Color:**
- White single actuator

Illuminated Actuator Color:

Green single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

- 3.094 inches
- **Inclosure Type:**
- Fully enclosed
- **Mounting Method:**
- Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 tab, solder lug and 12 turret

Specification Data:

81349-mil-s-22885/87 government specification

Shelf Life:

N/a

Unit Of Measure:

- **Demilitarization:**

NSN 5930-01-255-6166

Push Switch - Page 2 of 2

Fiig: A053a0

