## NSN 5930-01-255-8280

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-255-8280

### **Body Style:**

Panel mounted

## **Body Width:**

0.850 inches

## **Body Height:**

1.094 inches

## Actuator Length:

1.040 inches

## Actuator Style:

Rectangular

## Actuator Height:

0.140 inches

## Actuator Width:

0.800 inches

#### Actuator Color:

White single actuator and white single actuator

## **Illuminated Actuator Color:**

White single actuator and green single actuator

## Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Mounting Surface To Terminal End Distance:

3.094 inches

## Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

## **Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

## **Special Features:**

Horizontally split lens

## **Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

6 tab, solder lug and 6 turret

## **Specification Data:**

81349-mil-s-22885/87 government specification

## Shelf Life:

N/a

## Unit Of Measure:

# NSN 5930-01-255-8280

Push Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

