

View Online at <https://aerobasegroup.com/nsn/5930-01-255-8903>

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Distance Between Mounting Facility Centers:**

2.750 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

1000.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

0.4 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+4.00/+45.00 actuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point hex nut

**Contact Voltage Rating In Volts:**

480.0 ac at sea level first voltage

**Special Features:**

Designed to accommodate terminal board

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0