NSN 5930-01-255-8911

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-255-8911

| Body Style: |
|---|
| Bushing mounted |
| Overall Length: |
| 0.320 inches |
| Overall Height: |
| 0.825 inches |
| Overall Width: |
| 0.240 inches |
| Bushing Length: |
| 0.220 inches |
| Body Length: |
| 0.320 inches |
| Body Width: |
| 0.200 inches |
| Body Height: |
| 0.340 inches |
| Actuator Diameter: |
| 0.100 inches |
| |
| Actuator Height: 0.155 inches |
| |
| Maximum Voltage Rating In Volts: |
| 120.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 48 There de Circu |
| Thread Size: |
| 0.190 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Criticality Code Justification: |
| Zzzy |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 1.000 amperes resistive dc and 1.000 amperes resistive ac |
| Special Features: |
| Item must comply with requirements of defense supply center columbus production standard no. Lo3724 |
| Precious Material And Location: |
| Contact surfaces silver |
| Thread Series Designator: |

Uns

NSN 5930-01-255-8911

Push Switch - Page 2 of 2



| Terminal Type And | Quantity: |
|-------------------|-----------|
|-------------------|-----------|

3 tab, solder lug

Reference Number Differentiating Characteristics:

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Fiig:

No

A053a0