

View Online at <https://aerobasegroup.com/nsn/5930-01-256-0194>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

1.870 inches

Outside Diameter:

0.200 inches all connections

Overall Height:

0.670 inches

Overall Width:

1.011 inches

Body Length:

1.000 inches

Unthreaded Mounting Hole Diameter:

Between 0.101 inches and 0.107 inches

Longest Horizontal Distance Between Mounting Centers:

Between 0.771 inches and 0.791 inches

Longest Vertical Distance Between Mounting Centers:

Between 0.771 inches and 0.791 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

65.0 degrees celsius

Mounting Method:

Base and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

10.0 milliamperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+0.25/+0.35 actuation point inches of water

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

0.25 actuation point inches of water and 0.35 actuation point inches of water

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Pressure Connector Type:

Barbed, unthreaded external all connections

Special Features:

Adjustment screw hole filled to prevent tampering

Media For Which Designed:

Gas

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0