NSN 5930-01-256-0198

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-256-0198

· · · · · · · · · · · · · · · · · · ·						
Body Style:						
Hole mounted						
Hazardous Locations/environmental Protection:						
Explosion proof and watertight						
Overall Height:						
2.570 inches						
Overall Width:						
3.250 inches						
Actuator Length:						
2.500 inches						
Actuator Style:						
Roller arm						
Actuator Height:						
1.880 inches						
Actuator Roller Diameter:						
0.750 inches						
Actuator Roller Width:						
0.320 inches						
Housing Height:						
2.370 inches						
Housing Length:						
5.270 inches						
Housing Width:						
3.250 inches						
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:						
3.500 inches						
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:						
2.360 inches						
Maximum Voltage Rating In Volts:						
440.0 ac and 355.0 dc						
Inclosure Type:						
Fully enclosed						
Nonpile-up Contact Arrangement:						
1 two circuit, one position momentary single switch unit						
Switch Actuating Force:						
16.0 ounces						
Actuator Movement:						
10.0 pretravel degrees						
Contact Load Current Rating At Maximum Rated Voltage:						
100.000 milliamperes resistive dc and 6.000 amperes resistive ac						

4 screw

Terminal Type And Quantity:

NSN 5930-01-256-0198

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0