NSN 5930-01-256-1442

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-256-1442

| Body Style: |
|---|
| Bushing/hole mounted |
| Hazardous Locations/environmental Protection: |
| Watertight |
| Overall Length: |
| 1.950 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches |
| Overall Height: |
| 2.292 inches |
| Overall Width: |
| 0.690 inches |
| Body Length: |
| 1.950 inches |
| Body Width: |
| 0.690 inches |
| Body Height: |
| 0.980 inches |
| Case Material: |
| Metal |
| Actuator Style: |
| Roller plunger |
| Actuator Free Position Height: |
| 1.312 inches |
| Actuator Roller Diameter: |
| 0.500 inches |
| Actuator Roller Width: |
| 0.180 inches |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing and unthreaded hole |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.469 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action single switch unit |

Actuator Movement:

0.015 pretravel inches

NSN 5930-01-256-1442

Sensitive Switch - Page 2 of 2

Fiig: A053a0



| Contact Load Current Rating At Maximum Rated Voltage: |
|---|
| 15.000 amperes resistive dc |
| Thread Series Designator: |
| Uns |
| Terminal Type And Quantity: |
| 2 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |