NSN 5930-01-256-1442

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-256-1442

Body Style:
Bushing/hole mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
1.950 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
2.292 inches
Overall Width:
0.690 inches
Body Length:
1.950 inches
Body Width:
0.690 inches
Body Height:
0.980 inches
Case Material:
Metal
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.312 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.180 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing and unthreaded hole
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit

Actuator Movement:

0.015 pretravel inches

NSN 5930-01-256-1442

Sensitive Switch - Page 2 of 2

Fiig: A053a0



Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive dc
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No