

View Online at <https://aerobasegroup.com/nsn/5930-01-256-1546>

Thread Class:

2b 1st mounting facility

Thread Length:

0.438 inches 2nd mounting facility

Overall Length:

7.892 inches

Overall Height:

2.810 inches

Overall Width:

2.810 inches

Individual Section Quantity:

9

Longest Horizontal Distance Between Mounting Centers:

2.300 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.300 inches 2nd mounting facility

End Application:

Radio teletypewriter set an/grc-142c

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

0.905 inches 2nd mounting facility

Mounting Method:

Threaded stud 2nd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 1st mounting facility

Thread Size:

0.190 inches 2nd mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular 1st mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

7.5 amperes resistive load ac at sea level

Precious Material And Location:

Rotor and stator surfaces silver

Precious Material:

Silver

Style Designator:

Tap, square frame

Test Data Document:

81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf 2nd mounting facility

Specification Data:

81349-mil-s-21604/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0