NSN 5930-01-256-1558

Push Switch - Page 1 of 1

Fiig: A053a0



View Online at https://aerobasegroup.com/nsn/5930-01-256-1558 **Body Style:** Panel mount **Body Length:** 1.200 inches **Body Width:** 0.960 inches **Body Height:** 3.110 inches **Case Material:** Metal **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **End Application:** 1430-01-181-5884 battery command pos **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Nonpile-up Contact Arrangement:** 2 pole, double throw, both positions maintained single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 2.400 amperes lamp ac **Special Features:** Split lens **Test Data Document:** 81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 6 tab, solder lug and 6 turret **Specification Data:** 81349-mil-s-22885/9 government specification Shelf Life: N/a **Unit Of Measure: Demilitarization:** No