

View Online at <https://aerobasegroup.com/nsn/5930-01-256-3115>

Thread Class:

2b 1st mounting facility

Thread Length:

0.438 inches 2nd mounting facility

Overall Length:

7.750 inches

Overall Height:

2.812 inches

Overall Width:

2.812 inches

Individual Section Quantity:

10

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

12 each section periphery

Mounting Facility Circle Radius:

1.625 inches 1st mounting facility

Mounting Method:

Threaded stud 2nd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 1st mounting facility

Thread Size:

0.190 inches 2nd mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position circular 1st mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

7.5 amperes resistive load ac at sea level

Special Features:

Item must comply with requirements of desc production standard no. L03731; for navy nuclear propulsion plant products only

Style Designator:

Tap, square frame

Thread Series Designator:

Unf 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0