NSN 5930-01-257-2071

Thermostatic Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-257-2071 |
|---|
| Overall Length: |
| 2.875 inches |
| Overall Height: |
| 1.390 inches |
| Overall Width: |
| 1.656 inches |
| Distance Between Mounting Facility Centers: |
| 1.312 inches |
| Capillary Tube Length: |
| Between 35.0 inches and 37.0 inches |
| Bulb Length: |
| 4.438 inches |
| Bulb Diameter: |
| 0.375 inches |
| Tempurature Sensing Element Type: |
| Capillary tube-bulb |
| Mounting Method: |
| Bracket and threaded hole |
| Thready Qty Per Inch (tpi): |
| 32 single threaded hole |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.138 inches single threaded hole |
| Mounting Facility Pattern: |
| Two position in-line |
| Terminal Type: |
| Tab w/screw |
| Contact Load Current Rating: |
| 30.0 amperes resistive load single voltage |
| Contact Adjustability: |
| Actuation point adjustable |
| Contact Adjustment Range: |
| +85.00/+275.00 actuation point degrees fahrenheit |
| Contact Adjustment Type: |
| External actuation point shaft |
| Contact Voltage Rating In Volts: |
| 250.0 ac at sea level single voltage |

Gas or liquid

Style Designator:

Media For Which Designed:

Rectangular

NSN 5930-01-257-2071

Thermostatic Switch - Page 2 of 2



| Ī | hread | Series | Designator | r: |
|---|-------|---------------|------------|----|
| | | | | |

Unc single threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0